

## EQUIPMENT TYPE APPROVAL

### Distribution Customer Use

We hereby confirm that below detailed Equipment is in compliance with the latest relevant regulations and standards, therefore it is **Approved** to be used in Distribution Customer Installation for five years from issuance date, where expiry date is due the Approval Holder shall apply for renewal if needed.

Application Details	
Approval ID: <i>220613</i>	Approval Holder: <i>Schneider Electric</i>
Approval Type: <i>Distribution Customer Use</i>	Valid Till: <i>03 Nov 2027</i>
Equipment Details	
Category: <i>LV Switchgear &amp; Controlgear</i>	Trademark: <i>Schnieder Acti 9 IC60</i>
Description: <i>Annexure-A</i>	Designation: <i>Annexure-A</i>
Manufacture Details	
Name: <i>Schneider Electric Thailand Ltd</i>	Country of Origin: <i>Thailand</i>

**Comments:**

*EDD Requirements Fulfilled*

Signature:

Stamp:

Chief, Engineering Services Section



## TERMS AND CONDITIONS

1. The Directorate reserves the right to deny or disconnect electricity supply in case of any failure to comply with any compulsory provision of the latest relevant regulations and standards enforced by the Kingdom.
2. The Directorate retains the right to publish a censored copy of the approval.
3. The Approval Holder shall observe and adhere to the latest relevant regulations and standards.
4. The Approval Holder shall observe and adhere to the latest EDD Equipment Approval guidelines and instructions which are made available at EDD Equipment Approval Web Page.
5. The Approval Holder shall ensure that an Equipment is in compliance with the latest relevant regulations and standards, and it shall not cause any harm that endangers the safety of persons, property, or environment.
6. The Approval Holder shall ensure that all provided information are accurate, relevant, correct, and complete, and that the documents submitted along with the application are true, genuine, and authentic.
7. The Approval Holder shall provide any required information, documents, and samples necessary to demonstrate Equipment conformity with the latest relevant regulations and standards.
8. The Approval Holder is responsible for retaining all relevant information and documents for five years from issuance date.
9. The Approval Holder is responsible to present the approval in full without any omissions upon request.
10. The Approval is applicable whenever an Equipment is meeting the following provisions:
  - Classified in Applicable Standards List as Distribution Customer Use Equipment.
  - Meant to be used in Distribution Customer Installation.
11. The Approval Holder for this approval shall be Supplier licensed by MOIC to place Equipment on local market.
12. The Approval Holder shall apply for the approval before placing any Equipment on local market.
13. The Approval Holder is responsible to ensure that the approved Equipment is manufactured, tested, delivered, and stored in accordance with the latest relevant regulation and standards.
14. The Installation Contractor is responsible to ensure that an approved Equipment is installed in accordance with the latest relevant regulation and standards.

## ANNEXURE-A

No.	Description	Designation
1	6A RCBO,1P+N, Ue=110V/130V,30mA,6kA	XXXXXX
2	10A RCBO,1P+N, Ue=110V/130V,30mA,6kA	XXXXXX
3	16A RCBO,1P+N, Ue=110V/130V,30mA,6kA	XXXXXX
4	20A RCBO,1P+N, Ue=110V/130V,30mA,6kA	XXXXXX
5	25A RCBO,1P+N, Ue=110V/130V,30mA,6kA	XXXXXX
6	32A RCBO,1P+N, Ue=110V/130V,30mA,6kA	XXXXXX
7	40A RCBO,1P+N, Ue=110V/130V,30mA,6kA	XXXXXX
8	45A RCBO,1P+N, Ue=110V/130V,30mA,6kA	XXXXXX
9	6A RCBO,1P+N, Ue=240V,30mA,10kA	XXXXXX
10	10A RCBO,1P+N, Ue=240V,30mA,10kA	XXXXXX
11	16A RCBO,1P+N, Ue=240V,30mA,10kA	XXXXXX
12	20A RCBO,1P+N, Ue=240V,30mA,10kA	XXXXXX
13	25A RCBO,1P+N, Ue=240V,30mA,10kA	XXXXXX
14	32A RCBO,1P+N, Ue=240V,30mA,10kA	XXXXXX
15	40A RCBO,1P+N, Ue=240V,30mA,10kA	XXXXXX
16	45A RCBO,1P+N, Ue=240V,30mA,10kA	XXXXXX
17	6A RCBO,1P+N, Ue=240V,10mA,10kA	XXXXXX
18	10A RCBO,1P+N, Ue=240V,10mA,10kA	XXXXXX
19	16A RCBO,1P+N, Ue=240V,10mA,10kA	XXXXXX
20	20A RCBO,1P+N, Ue=240V,10mA,10kA	XXXXXX
21	25A RCBO,1P+N, Ue=240V,10mA,10kA	XXXXXX
22	32A RCBO,1P+N, Ue=240V,10mA,10kA	XXXXXX
23	40A RCBO,1P+N, Ue=240V,10mA,10kA	XXXXXX
24	45A RCBO,1P+N, Ue=240V,10mA,10kA	XXXXXX
25	6A RCBO,1P+N, Ue=240V,100mA,10kA	XXXXXX
26	10A RCBO,1P+N, Ue=240V,100mA,10kA	XXXXXX
27	16A RCBO,1P+N, Ue=240V,100mA,10kA	XXXXXX
28	20A RCBO,1P+N, Ue=240V,100mA,10kA	XXXXXX
29	25A RCBO,1P+N, Ue=240V,100mA,10kA	XXXXXX
30	32A RCBO,1P+N, Ue=240V,100mA,10kA	XXXXXX
31	40A RCBO,1P+N, Ue=240V,100mA,10kA	XXXXXX
32	45A RCBO,1P+N, Ue=240V,100mA,10kA	XXXXXX
33	10A RCBO,2P, Ue=240V,30mA,10kA	XXXXXX
34	16A RCBO,2P, Ue=240V,30mA,10kA	XXXXXX
35	20A RCBO,2P, Ue=240V,30mA,10kA	XXXXXX
36	25A RCBO,2P, Ue=240V,30mA,10kA	XXXXXX
37	32A RCBO,2P, Ue=240V,30mA,10kA	XXXXXX
38	10A RCBO,2P, Ue=240V,300mA,10kA	XXXXXX
39	16A RCBO,2P, Ue=240V,300mA,10kA	XXXXXX
40	20A RCBO,2P, Ue=240V,300mA,10kA	XXXXXX

## ANNEXURE-A

No.	Description	Designation
41	25A RCBO,2P, Ue=240V,300mA,10kA	XXXXXX
42	32A RCBO,2P, Ue=240V,300mA,10kA	XXXXXX