

Appendixes


A - K

Appendixes

Thermal Insulation Implementation Forms & Templates for Buildings of 2800sqm and above

Appendix-A	Thermal Insulation Implementation Form	Page 3 to 11
Appendix-B	Calculation Sheet for Glass Area	Page 12
Appendix-C	Calculation Sheet for External Surface Area	Page 14
Appendix-D	Follow Up Notice	Page 15
Appendix-E	Material Approval Form for Glass	Page 16
Appendix-F	Certificate to be given by Glass Supplier/Fabricator	Page 17
Appendix-G	Thermal Insulation Implementation Modification Form	Page 18 to 27
Appendix-H	Check List for TII Modification Form	Page 28
Appendix-J	Form to be submitted for change of Engineering Office	Page 29
Appendix-k	Overall U-value Calculations for External Walls	Page 30 to 33

APPLICATION NO.

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

THERMAL INSULATION IMPLEMENTATION FORM

Client Name: Phone No.: e-mail:
Bldg. No. Road No. Block No. Area:
Engineering Office Name: Phone No.:
Building Type: No. of floors:

• *Thermal Transmittance (U-Value) for Roofs*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (I) m	r	R	Notes
				<u>m.k</u>	<u>m².k</u>	
				w	w	
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
Total thermal resistances for materials used in Roof (R _T):						

U-Value = W/m.² °C


Client's Name
& Signature

In-charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

- *Thermal Transmittance (U-Value) for Air-conditioned floors/ceilings exposed to non-air-conditioned spaces*

Sr. No.	Description of materials used	Density kg/m ³	Thickness	r	R	Notes
			(I)	<u>m.k</u>	<u>m².k</u>	
			m	w	w	
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value = W/m.² °C


**Client's Name
& Signature**

**In charge Engineer
Name & Signature**

**Engineering Office
Stamp & Signature**

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for external Walls with Blocks*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (l) m	$\frac{r}{m.k}$ w	$\frac{R}{m^2.k}$ w	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R _T):						

U-Value = W/m.² °C


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for Concrete/ Shear Walls*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (I) m	$\frac{r}{m.k}$ w	$\frac{R}{m^2.k}$ w	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R _T):						

U-Value = W/m.² °C


**Client's Name
& Signature**

**In charge Engineer
Name & Signature**

**Engineering Office
Stamp & Signature**

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for External Columns*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (I) m	r $\frac{m.k}{w}$	R $\frac{m^2.k}{w}$	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value =	W/m.² °C
------------------	----------------------------


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for External Beams*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (l) m	$\frac{r}{m.k}$ w	$\frac{R}{m^2.k}$ w	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value =	W/m.² °C
------------------	----------------------------


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for Spandrel Area of Curtain Wall*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (l) m	$\frac{r}{m.k}$ w	$\frac{R}{m^2.k}$ w	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R _T):						

U-Value = W/m. ² °C


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

- *Thermal Transmittance (U-Value) for walls of light wells/shafts/voids*

Sr. No.	Description of materials used in Walls	Density kg/m ³	Thickness (l) m	r $\frac{m.k}{w}$	R $\frac{m^2.k}{w}$	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value =	W/m.² °C
------------------	----------------------------


**Client's Name
& Signature**

**In charge Engineer
Name & Signature**

**Engineering Office
Stamp & Signature**

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

- *Thermal Transmittance (U-Value) for* *(specify the type of wall)*

Sr. No.	Description of materials used in Exterior Walls	Density kg/m ³	Thickness (l) m	$\frac{r}{m.k}$ w	$\frac{R}{m^2.k}$ w	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value = W/m.² °C


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

Glass Selection Details

Location	Windows & Doors	Curtain Wall	Sky Light	Total Glass Area (M ²)	Total Surface Area (M ²)	Glass %
Glass Area (M ²)						

LOCATION	GLASS MAKE/DESCRIPTION/COATING SURFCE #		THICKNESS (mm)			SUMMER U-VALUE (W/M ² °C)	SHADING COEFFICIENT (SC)	LIGHT TRANSMITTANCE %
	OUTER GLASS	INNER GLASS	OUTER GLASS	AIR SPACE	INNER GLASS			
WINDOWS & DOORS								
CURTAIN WALLS								
SKY LIGHT								

I hereby state that all information in the attached tables and documents is correct and I confirm that I will comply with Thermal Insulation Order no. (8 /99) for the construction of this building.

**Client's Name
 & Signature**

**In-charge Engineer
 Name & Signature**

**Engineering Office
 Stamp & Signature**

Electricity & Water Authority Approval

Where: (U) = $\frac{1}{R_T}$ W/m.²k

Date of Approval

$R_{T=}$ Total thermal resistance's: $(R_T) = R_o + R_i + R_1 + R_2 + R_3 + \dots = (m.^2k/w)$

Thermal resistance for adjacent air layer (m.²k/w)

Section	Thermal resistance for adjacent air layer	
	Interior thermal resistance (R _i)	Outside thermal resistance (R _o)
Wall	0.121	0.059
Roof	0.166	0.059

THERMAL INSULATION IMPLEMENTATION
CALCULATION SHEET FOR GLASS AREA

Job Title: _____ Client's Name: _____

Type of External Glazed Window/Glazed Door/Curtain wall/Sky light	Size of window/door /curtain wall/sky light (W x H)	Front Elevation		Rear Elevation		Left Elevation		Right Elevation		Total Glass Area of all Elevations (M ²)	Total Surface Area of all Elevations (M ²)
		Qty (N _f)	Total Glass Area (M ²) (WxHxN _f)	Qty (N _r)	Total Glass Area (M ²) (WxHxN _r)	Qty (N _l)	Total Glass Area (M ²) (WxHxN _l)	Qty (N _{ri})	Total Glass Area (M ²) (WxHxN _{ri})		
Total glass area in each elevation (G _a)											
Surface area of each elevation (S _a)											
Percentage of Glass (G _a /S _a)X100											

Engineering Office Name: _____

Incharge Engineer's Name: _____

Incharge Engineer's Signature: _____

Notes:

1. Indicate type of window/door/curtain wall/sky light as W_n/D_n/CW_n/SKL_n respectively. n is variable as per schedule of windows, doors, curtain wall and sky light. Use additional sheets if required.
2. For windows facing light wells, submit separate calculation sheet.

CALCULATION SHEET FOR EXTERNAL SURFACE AREAS (including glass)

Floor Designation	Front		Rear		Left		Right	
	LxHxN*	Area (M ²)	LxHxN*	Area (M ²)	LxHxN*	Area (M ²)	LxHxN*	Area (M ²)
Ground Floor								
Mezanine Floor								
Typical Floors								
Roof Deck								
Pent House								
Other Floors								
Total area								

Engineering Office Name: _____

Incharge Engineer's Name: _____

Incharge Engineer's Signature: _____

Notes:


L= Length (Meters) H= Hight (Meters)

N* = No. of Typical Floors and is applicable for calculating total surface area of typical floors. For remaining floors N*=1

Other floors: Specify & add if any

Exclude basement, car park levels & parapet in calculation of external surface areas.

Submit separate calculation sheet for light wells.

Kingdom of Bahrain		ملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

FOLLOW-UP NOTICE FOR
THERMAL INSULATION IMPLEMENTATION

TO:

ELECTRICITY & WATER CONSERVATION DIRECTORATE

ELECTRICITY & WATER AUTHORITY

FAX: 17006349

Application No.: _____ **Building Permit No.** _____

Client Name: _____

Building No. _____ **Road No.** _____ **Block No.** _____ **Area** _____

We would like to inform you that we are going to start the installation of thermal insulation for the (Roof / Wall/Glass) of floor no. on and that the thermal insulation will not be covered before

Name & Signature of supervising Engineer:

Telephone No.:

Engineering Office Name & Stamp:

Date:

Note:

This form should be sent for each floor/roof/glass when intending to start the installation of thermal insulation and at least two weeks before its completion.

Copies of building permission & address card for entrance should be sent with the first Follow up Notice.



Thermal Insulation Implementation Program Material Approval Form for Glass

Application # _____ Owner's Name _____

Engineering Office Name: _____

Date of Submission: _____

We submit following details for the Glass to be used in the above project for approval:

Manufacturer & Brand		
Local Agent of Manufacturer/Supplier & their Tel No.		
Aluminum Fabricator & Tel No.		
Product Description of glass for windows/doors .		
Product Description of glass for curtain wall..		
Product Description of glass for skylight..		
Expected start date of fabrication:*		
Documents/Samples to be submitted with this Form:	<ul style="list-style-type: none"> Performance Data from Manufacturer for each type of glass. Certificate from the local supplier & Fabricator as per the format enclosed. One Sample for each type duly labeled with following details: <ul style="list-style-type: none"> - Engineering Office: - TII Application No.: - Project Name: - Client Name: - Glass Make & Product description: - Supplier/ Aluminum Fabricator details: 	
Client's Name & Signature	Engineer in Charge Name & Signature	Engineering Office Stamp & Signature
EWA Approval::		
Approved/Rejected	Remarks:	
Signature:	Stamp	
Date:		

- Engineering Office to send Follow Up Notices for inspection of glass at the factory of the Fabricator and at the building site at least one week before the start of Fabrication/installation of the glass.. Approved glass sample(s) should be available at building site till the final inspection of glass.
- Copies of delivery notes from the glass manufacturer to local supplier and from the local supplier to Aluminum Fabricator should be submitted to EWA at the time of inspection of glass.

Certificate to be given by the Glass Supplier & Aluminium Fabricator

Project Name: _____
 Client : _____
 Engineering Office: _____

Thermal Insulation Application No.: _____

We hereby confirm that the glasses supplied/used for windows/curtain walls/skylight for the above project are as given below:

Location	Make/Brand	Glass description & coating surface #		Thickness (mm)		
		Outer glass	Inner glass	Outer glass	Air Space	Inner glass
Windows						
Curtain walls.						
Skylight.						
Glass received from: Delivery Note No(s)& Date(s)*:						
Date the glass would be ready for inspection by E.O & MEW*:						


Signature: _____

Name: _____

Designation: _____

Company Stamp

Glass supplier should refer the thermal insulation application No. in their delivery notes to the aluminium fabricator.

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

THERMAL INSULATION IMPLEMENTATION
MODIFICATION FORM

To : Electricity & Water Conservation Directorate

We would like to inform you about the following changes in our Application No. _____

Date Approved _____

- | | |
|--|--|
| <input type="checkbox"/> Owner
<input type="checkbox"/> Insulation Materials in Roof
<input type="checkbox"/> Glass Type | <input type="checkbox"/> Engineering Office
<input type="checkbox"/> Insulation Materials in walls
<input type="checkbox"/> Glass Area |
|--|--|

• *Thermal Transmittance(U-value) for Roof*

Sr. No.	Description of materials used in Roof	Density kg/m ³	Thickness (I) m	r	R	Notes
				<u>m.k</u>	<u>m².k</u>	
				w	w	
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
Total thermal resistances for materials used in Roof (R _T):						

U-Value = W/m. ² °C


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

- *Thermal Transmittance (U-Value) for Air-conditioned floors/ceilings exposed to non-air-conditioned spaces*

Sr. No.	Description of materials used	Density kg/m ³	Thickness	r	R	Notes
			(I)	<u>m.k</u>	<u>m².k</u>	
			m	w	w	
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value = W/m.² °C


**Client's Name
& Signature**

**In charge Engineer
Name & Signature**

**Engineering Office
Stamp & Signature**

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for external Walls with Blocks*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (l) m	$\frac{r}{w}$ $\frac{m.k}{w}$	$\frac{R}{w}$ $\frac{m^2.k}{w}$	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value =	W/m.² °C
------------------	----------------------------


**Client's Name
 & Signature**

**In charge Engineer
 Name & Signature**

**Engineering Office
 Stamp & Signature**

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for Concrete/ Shear Walls*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (l) m	$\frac{r}{w}$ m.k	$\frac{R}{w}$ m ² .k	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R _T):						

U-Value = W/m.² °C


**Client's Name
& Signature**

**In charge Engineer
Name & Signature**

**Engineering Office
Stamp & Signature**

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for External Columns*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (I) m	$\frac{r}{w}$ m.k	$\frac{R}{w}$ m ² .k	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R _T):						

U-Value =	W/m. ² °C
-----------	----------------------


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for External Beams*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (I) m	$\frac{r}{m.k}$ w	$\frac{R}{m^2.k}$ w	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R _T):						

U-Value =	W/m.² °C
------------------	----------------------------


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

• *Thermal Transmittance (U-Value) for Spandrel Area of Curtain Wall*

Sr. No.	Description of materials used	Density kg/m ³	Thickness (l) m	$\frac{r}{w}$ m.k	$\frac{R}{w}$ m ² .k	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R _T):						

U-Value = W/m.² °C


**Client's Name
& Signature**

**In charge Engineer
Name & Signature**

**Engineering Office
Stamp & Signature**

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

Thermal Transmittance (U-Value) for walls of light wells/shafts/voids

Sr. No.	Description of materials used in Walls	Density kg/m ³	Thickness (I) m	$\frac{r}{m.k}$ w	$\frac{R}{m^2.k}$ w	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value =	W/m.² °C
------------------	----------------------------


Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

- **Thermal Transmittance (U-Value) for** *(specify the type of wall)*

Sr. No.	Description of materials used in Exterior Walls	Density kg/m ³	Thickness (I) m	$\frac{r}{w}$ $\frac{m.k}{w}$	$\frac{R}{w}$ $\frac{m^2.k}{w}$	Notes
1-						
2-						
3-						
4-						
5-						
6-						
7-						
8-						
9-						
10-						
11-						
12-						
13-						
Total thermal resistance for materials used in Wall (R_T):						

U-Value = W/m.² °C
--


**Client's Name
 & Signature**

**In charge Engineer
 Name & Signature**

**Engineering Office
 Stamp & Signature**

Electricity & Water Authority Approval

Date of Approval

Kingdom of Bahrain		مملكة البحرين
Electricity & Water Authority		هيئة الكهرباء والماء
Electricity & Water Conservation Directorate		إدارة ترشيد الكهرباء والماء

Glass Selection Details								
Location	Windows & Doors	Curtain Wall	Sky Light	Total Glass Area (M ²)	Total Surface Area (M ²)	Glass %		
Glass Area (M ²)								
LOCATION N	GLASS MAKE/DESCRIPTION/COATING SURFCE #		THICKNESS (mm)			SUMMER U-VALUE (W/M ² °C)	SHADING COEFFICIENT (SC)	LIGHT TRANSMITTANCE %
	OUTER GLASS	INNER GLASS	OUTER GLASS	AIR SPACE	INNER GLASS			
WINDOWS & DOORS								
CURTAIN WALLS								
SKY LIGHT								

I hereby state that all information in the attached tables and documents is correct and I confirm that I will comply with Thermal Insulation Order no. (8 /99) for the construction of this building.

Client's Name
& Signature

In charge Engineer
Name & Signature

Engineering Office
Stamp & Signature

Electricity & Water Authority Approval

Date of Approval

CHECK LIST FOR THERMAL INSULATION IMPLEMENTATION (TII)-MODIFICATION FORM

Engineering Office shall ensure that the modification form is complete with all details given below and attach supporting documents and drawings as required. Two sets are to be submitted.

1	Application No. as given in the approved TII Form	
2	Tick the appropriate box for the type of changes proposed	
3	For change of owner, attach supporting document for transfer of ownership, copy of CPR/CR, Tel No.& e-mail for the new owner	
4	For change of Engineering Office, submit "Form to be submitted with TII Modification for change of Engineering Office".	
5	For change of insulation materials in roof, attach drawing for roof cross section and supporting documents for resistivity values of new materials proposed in the roof.	
6	For change of insulation materials in walls, attach drawing for wall cross section and supporting documents for resistivity values of new materials proposed in the walls.	
7	For change of glass type, attach drawing for glass cross section, copy of performance data sheet from the manufacturer's catalogue for the new type of glass. High light, in the performance data sheet, the glass proposed to be used. Glass selection should be in accordance with Table (5.2) in the Code of Practice for thermal insulation in buildings.	
8	For change of glass area, attach revised floor plans, elevations, schedule of doors & windows and calculation sheets for glass/external surface areas, details for glass selected. Attach copy of performance data sheet from the manufacturer.	

Notes:

All the pages of the modification form duly filled with relevant information and with names and signatures of client, in-charge engineer, stamp & signature of engineering office should be submitted. If there is no change in any of the pages of the previously approved TII Form, information given in the approved TII Form shall be repeated in these pages and signed afresh by all concerned.

If wall/roof construction is different at different locations, then additional sheets for roof/wall with relevant data for each such construction/location should be included.



**FORM TO BE SUBMITTED WITH THERMAL INSULATION IMPLEMENTATION
MODIFICATION FOR CHANGE OF ENGINEERING OFFICE**

TII Application #. _____ Building Permit # _____

1st Engineering Office Name: _____

Supervision start date: _____ Supervision end date: _____

We confirm that thermal insulation requirements as per the approved TII Form have been implemented & inspected by EWA at the following locations in the building as on the end date of our supervision:.

Walls: (Floor Nos.):. Roof: Yes/No Glass: Yes/No

Others:

Thermal insulation is yet to be implemented at the following locations of the building as on the end date of our supervision:

Walls: (Floor Nos.):. Roof Glass

Others:

Pending violations*:

:
Owner's Name & Signature In-charge Engineer Engineering Office
Name & Signature Name & Signature Stamp & Signature

2nd Engineering Office Name: _____ Supervision start date: _____

We confirm that we inspected the building and will take full responsibility for the implementation of thermal insulation in the building as per attached TII Modification Form submitted for approval. We undertake to rectify pending violations.

Owner's Name & Signature In-charge Engineer Engineering Office
Name & Signature Name & Signature Stamp & Signature

* Give details of pending violations notified by EWA.

Engineering Office should notify EWA by fax (Fax No. 17006349) immediately when their supervision contract is terminated.

OVERALL U-VALUE CALCULATION FOR EXTERNAL WALLS

Client Name: _____ **Block No.:** _____ **No. of floors:** _____

Type of external wall	Area M² (A)	U-Value (U)	A*U
Wall with blocks			
Concrete shear wall			
External Columns			
External Beams			
External Lintels/Sill Beams			
Spandrel area of curtain wall			
Walls of light wells/shafts/voids			
Other type of walls			
Total	A_T		A*U_T
Overall U-value			A*U_T/A_T

Engineering Office Name: _____

Incharge Engineer's Name: _____

Incharge Engineer's Signature: _____

Note:

Exclude area of glazed doors/windows/vision glass of curtain walls from total area A_T

AREA CALCULATIONS-SHEAR WALLS/WALLS WITH BLOCKS

Client Name: _____ **Block No.:** _____ **No. of floors:** _____

SHEAR/CONCRETE WALLS				WALLS WITH BLOCKS			
Location		Length (M)	Height (M)	Area M2	Length (M)	Height (M)	Area M2
GF	North						
	East						
	West						
	South						
Typical Floors	North						
	East						
	West						
	South						
Roof Deck	North						
	East						
	West						
	South						
Other Floors	North						
	East						
	West						
	South						
Total					Total		

Engineering Office Name: _____

Engineering Office Name: _____

Incharge Engineer's Signature: _____

AREA CALCULATIONS-EXTERNAL COLUMNS/BEAMS/LINTELS/SILL BEAMS

Client Name:

Block No.:

No. of floors:

COLUMNS					BEAMS					LINTELS/SILL BEAMS				
Type	Width (M)	Height (M)	No,	Area M ²	Type	Length (M)	Height (M)	No,	Area M ²	Type	Width (M)	Height (M)	No,	Area M ²
C1					B1					L1				
C2					B2					L2				
C3					B3					L3				
										SBI				
										SB2				
										SB3				
Total					Total					Total				

Engineering Office Name:

Incharge Engineer's Name:

Incharge Engineer's Signature:

AREA CALCULATIONS-GLAZING

Client Name: _____

Block No.: _____

No. of floors: _____

CW Type	CURTAIN WALL				GLAZED DOORS/WINDOWS				Type	Length (M)	Height (M)	No,	Area M ²
	Vision Glass		Spandrel		Length (M)	Height (M)	No,	Area M ²					
	Length (M)	Height (M)	No,	Area M ²									
CW1									D1				
CW2									D2				
CW3									D3				
									W1				
									W2				
Cn									Wn				
Total				Total				Total					

Engineering Office Name: _____

Incharge Engineer's Name: _____

Incharge Engineer's Signature: _____